

THE ACM DIGITAL LIBRARYTerms used [cross](#) [capacitance](#) [model](#) [string](#)

Found 35 of 141,680

Sort results by

 Save results to a Binder[Try an Advanced Search](#)

Display results

 [Search Tips](#)[Try this search in The ACM Guide](#) Open results in a new window

Results 1 - 20 of 35

Result page: 1 [2](#) [next](#)Relevance scale **1 Modeling and analysis of differential signaling for minimizing inductive cross-talk**

Yehia Massoud, Jamil Kawa, Don MacMillen, Jacob White

June 2001 **Proceedings of the 38th conference on Design automation**Full text available:  [pdf\(260.44 KB\)](#)Additional Information: [full citation](#), [abstract](#), [references](#), [citations](#), [index terms](#)

Many physical synthesis tools interdigitate signal and power lines to reduce cross-talk, and thus, improve signal integrity and timing predictability. Such approaches are extremely effective at reducing cross-talk at circuit speeds where inductive effects are inconsequential. In this paper, we use a detailed distributed RLC model to show that inductive cross-talk effects are substantial in long busses associated with 0.18 micron technology. Simulation experiments are then used to demon ...

2 Operational features of an MOS timing simulator

P. Kozak, H. K. Gummel, B. R. Chawla

January 1975 **Proceedings of the 12th conference on Design automation**Full text available:  [pdf\(524.38 KB\)](#)Additional Information: [full citation](#), [abstract](#), [references](#), [citations](#), [index terms](#)

This paper describes operational features of a timing simulator having performance characteristics between those of circuit analysis programs and conventional logic simulators.

3 Operational features of a MOS timing simulator

P. Kozak, H. K. Gummel, B. R. Chawla

June 1988 **Papers on Twenty-five years of electronic design automation**Full text available:  [pdf\(657.10 KB\)](#)Additional Information: [full citation](#), [references](#), [index terms](#)**4 Interaction and modeling techniques for desktop two-handed input**

Ken Hinckley, Mary Czerwinski, Mike Sinclair

November 1998 **Proceedings of the 11th annual ACM symposium on User interface software and technology**Full text available:  [pdf\(212.66 KB\)](#)Additional Information: [full citation](#), [references](#), [citations](#), [index terms](#)

Keywords: TouchMouse, input devices, map navigation, tablests, three-state model, touchpads, two-handed input

5 Simultaneous shield insertion and net ordering for capacitive and inductive coupling minimization

**Welcome to IEEE Xplore**

- [Home](#)
- [What Can I Access?](#)
- [Log-out](#)

Tables of Contents

- [Journals & Magazines](#)
- [Conference Proceedings](#)
- [Standards](#)

Search

- [By Author](#)
- [Basic](#)
- [Advanced](#)

MEMBER SERVICES

- [Join IEEE](#)
- [Establish IEEE Web Account](#)
- [Access the IEEE Member Digital Library](#)

ENTERPRISE SERVICES

- [Access the IEEE Enterprise File Cabinet](#)

Print Format

9-7-2004

L Number	Hits	Search Text	DB	Time stamp
1	1	string same model same cross same capacitance	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM TDB	2004/09/07 13:09

L Number	Hits	Search Text	DB	Time stamp
1	1	string same model same cross same capacitance	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM TDB USPAT	2004/09/07 13:09
2	490	(703/14).CCLS.	USPAT	2004/09/07 13:10
3	0	((703/14).CCLS.) and (cross adj capacitance)	USPAT	2004/09/07 13:10
4	17	((703/14).CCLS.) and (cross same capacitance)	USPAT	2004/09/07 13:10